To protect the privacy of customers or suppliers of Salamander Jewelry. We erased their address from this document.

CUSTOMER :

COMMODITY: Stainless Steel Cold Drawn Round Bar (R)

CERTIFICATE NO: A1706160069

ORDER NO.: 10605A067/

SPECIFICATION: 304/304L

LENGTH TOLERANCE: 0-50

DOC No. .

LC NO: MD1CF706NU00089

SUPPLY CONDITION: CD

DATE OF ISSUE: 2017/06/16

Heat 1	No	Thick (Dia)	Pcs	₩t		Chemical Composition(wt%) Mechanical Property																		
		(mm)		(kg)	С	Si	Mn	P	S	Ni	Cı	Mo	Cu	N				TS	YS	EL	RA	HRB	HRC	
					x100	x100	λ100	x1000	x1000	x100	x100	x100	x100	x10000				N/mm2	N/mm2	%	H			
Spec	Min									800	1800							620	310	30	40			
	Max				3	100	200	45	30	1200	2000			1000										
5G807		12.00		2760	1.7	32	161	28	26.8	806	1812	9	49	813				736	634	45	70	96		

Total:

TOLERANCE: h9

2760

and radiation contamination. Qualification

No. of Taiwan Atomic Energy Committee: 136

4. No welding repaired

3. The Above Testing Results Relate Only To The Items Tested.

To protect the privacy of customers or suppliers of Salamander Jewelry.
We erased their address from this document.

Acc. to ASTM A276 Cond. A The hardness conform to the requirement of raw material on NACE MR0103 and MR0175-A2. The chemistry conform to the requirement of raw material on NACE MR0103 and MR0175-D1. This inspection certificate is issued according to EN 10204 2.2 Remark: SUPPLY CONDITION: We have the following certifications Melted manufactured : Taiwan Improved machining. A:Annealed 1.ISO9001:2015 Quality Management System B:Shot Blasted Solution annealed treatment: Acc. to ASTM A484. 2.ISO/IEC 17025:2005 Laboratory Management System C:As Casted Micro structure: good., Grain size: Acc. to ASTM E112. E:Reeled/Skin Pass 3.PED & AD2000-Merkblatt W0 H:Precipitation Hardening 4.DNV . LR . ABS Classification Society certification HR:Hot Rolled 5.ISO14001:2004 Environment Management System I:Straightened 6.OHSAS 18001:2007 & TOSHMS Certificate K:Cut Edge L:Polished 1. We hereby certify that material described herein has been M:Cold Rolled manufactured and tested with satisfactory results P:Pickled in accordance with requirement S:Shaved TEST METHOD : V:Slit of the above material specification. CHEMICAL-ASTM E1806, E415, E1086, E1019 W:Cut 2. We certify that the material is free from mercury X:Temper

CD:Cold Draw

CG:Centerless Ground

PL:Turned or Peeled

To protect the privacy of customers or suppliers of Salamander Jewelry.

We erased their address from this document.